

### AMENDMENTS TO THE CLAIMS

1. (Currently amended) A process for the production of high-octane gasoline from a hydrocarbon feed stream with C<sub>4+</sub> hydrocarbons cuts comprising contacting the feed under isomerisation conditions with a catalyst composition consisting of mixed aluminium and zirconium oxides modified with tungsten oxyanion and ~~hydrogenation/dehydrogenation component of a Group~~~~oup~~ VIII metal platinum and/or palladium.

2. (Original) A process according to claim 1, wherein the hydrocarbon feed contains at least 20 wt % of C<sub>7+</sub> hydrocarbons.

3. (Previously presented) A process according to claim 1, wherein the isomerisation conditions comprise presence of hydrogen with a hydrogen to hydrocarbon molar ratio between 0.1 to 5, a temperature range from 150 °C to 300 °C, a total pressure of between 1 and 40 bar and a liquid space velocity LHSV of between 0.1 to 30 h<sup>-1</sup>.

4. (Currently amended) A process according to claim 1, wherein the catalyst composition in its dry form comprises 10-50 wt % of tungsten oxide, 10-40 % of aluminium oxide and a remainder of zirconia and ~~Group~~~~oup~~ Group VIII metal.

5. (Currently amended) A process according to claim 1, wherein the ~~Group~~~~oup~~ VIII metal is platinum and/or palladium is in an amount of between 0.01 wt % to 5 wt %.